

FD30T Forklift



Introduction of Forklift of Forklift:

1. FD30T forklift is a kind of spade machine used in construction industry both China and abroad.
2. This kind of forklift has beautiful appearance, optimized by computer.
3. FD30T forklift is configured according to international standard, it is safe while operating. The forklift can protect environment against pollution.
4. The forklift is working with high efficiency by combining manual operation and mechanized operation.
5. FD30T forklift is configured according to international standard; it is safe to be operated. The forklift can protect environment against pollution.
5. The optimized combined operating system in forklift makes the operation much convenient.

Specifications of FD30T Balanced Internal Combustion Forklift:

Model	FD30T
Rated capacity	3000 kg
Load center	500 mm
Power type	Diesel engine
Control	Sit down rider type
Gear type	Hydraulic
Max. driving speeds(with/without load)	17/19(km/h)
Max. lifting speeds(with load)	430 mm/s
Max traction	13 KN
Max. grade ability with load	20 °
Max. lift height	3000 mm
Free lift height	160 mm

Mast tilt angle (F/R)	6/12 °
Overall length with forks	3750 mm
Overall width	1225 mm
Mast height	2065 mm
Overall height, fork raised	4272 mm
Overhead guard height	2100 mm
Turning radius	2460 mm
Fork overhang	490 mm
Passage width (basic right angle stow)	2110mm
Front tires	28x9-15-12PR
Rear tires	6.50-10-10PR
Thread Front/Rear	1000/970 (mm)
Wheelbase	1700 mm
Ground clearance at mast	140 mm
Ground clearance at frame	150 mm
Service brake	Hydraulic/foot pedal
Parking brake	Mechanical/hand lever
Operating weight	4360 kg